



# DL8700

## *Vehicle Mounted Terminal*

### FEATURES



- WLAN IEEE 80.11b or OpenAir Standard
- Full terminal emulation support
- IP66 protection class
- First-class electroluminescent (EL) display 640 X 200 pixels
- Large and intuitive QWERTY or ABCD keyboard
- Vibration proof

### APPLICATIONS

- Warehousing
- In-outdoor data collection
- Yard management

### GENERAL DESCRIPTION

Datalogic is proud to introduce the **DL8700**, the vehicle mounted RF computer. Designed and built for rugged environments, the **DL8700** provides a superior protection class for applications in extremely harsh environments (IP66). Its architecture is powered by a 32-bit microprocessor, with electro-luminescent waterproof display (1/2 VGA) and full keyboard for easy data entry. A choice between a QWERTY or ABCD keyboard is available to meet any user requirements. Thanks to its particular mounting bracket, the **DL8700** is also immune to vibrations and mechanical shocks.

Communication is extremely flexible and compliant with all emerging technologies and different vendors. Datalogic supplies RF WLAN technology, compliant with the IEEE 802.11b standard including Voice over IP support, and OpenAir.

Communication management to the legacy system takes advantage of the new software product line which includes terminal emulation connectivity for OS/400, Unix, Microsoft Windows platforms, including the most used ERPs, such as SAP R/3. In addition, the **DL8700** can be used in combination with the Dragon™ laser gun to allow automatic data entry; both cabled and cordless versions of the Dragon™ can be used. With the cabled version the Dragon™ can be directly powered by the **DL8700** serial connector, simplifying the installation procedure.

The **DL8700** is a powerful, sturdy VMT solution for any warehousing application.



## MODELS



### RADIO TYPE

- Proxim (EU, FR, SP)
- Cisco (EU, FR)
- Lucent (EU, FR)

### KEYBOARD

- QWERTY
- ABCD

### EMULATION

- IBM5250
- ANSI+ (VT/HP)

## SPECIFICATIONS

### PHYSICAL CHARACTERISTICS

DIMENSIONS	229 x 305 x 83 mm (H x W x D)
WEIGHT	Approx. 2.268 Kg
ENCLOSURE	Combination High Impact Black polycarbonate/polyester blend plastic and aluminium casting
OPERATING TEMPERATURE	-20 to 50 °C (-4 to 122 °F)
STORAGE TEMPERATURE	-20 to 70 °C (-4 to 158 °F)
VIBRATION RESISTANCE	Based on MIL STD 810D
ENVIRONMENTAL SEALING	IP66, sealed against water and dust
DISPLAY	Super Bright Electroluminescent (EL) 640 x 200 pixels
POWER	10 - 80 Vdc Internal and NiCd back-up battery
KEYBOARD	Integrated QWERTY or ABCD with specific overlay for emulation

### PERFORMANCE

MICROPROCESSOR	Intel® 486 SX ULP
OPERATING SYSTEM	Phoenix PICO BIOS®
SYSTEM RAM MEMORY	4 MB
SYSTEM FLASH MEMORY	8 MB
INTERFACES	Electrical: 2 RS 232 DA-9 with 5 U power options

### RF DATA COMMUNICATION

NETWORK	WLAN, IEEE 802.11b or OpenAir compliant
ANTENNA	External
FREQUENCY RANGE	Country dependent, typically 2.4 to 2.5 GHz



Product and company names and logos referenced may be either trademarks or registered trademarks of their respective companies

We reserve the right to make modifications and improvements

**Datalogic S.p.A.**  
Italy  
Corporate Headquarters  
Tel. +39 051/3147011  
Fax +39 051/726562  
info@datalogic.it

**Sales Italy**  
Tel. +39 051/3147011  
Fax +39 051/3147170  
venditeitalia@datalogic.it

**Sales International**  
(Central and South America,  
Far East, Middle East - Africa)  
Tel. +39 041/5986511  
Fax +39 041/5986550  
sales-intl@datalogic.it

**Australia**  
Datalogic PTY LTD.  
Tel. +61 3/95589299  
Fax +61 3/95589233  
sales@datalogic.com.au

**Germany**  
Datalogic GmbH  
Tel. +49 7026/6080  
Fax +49 7026/5746  
info@datalogic.de

**Sweden**  
Datalogic AB  
Tel. +46 40/385000  
Fax +46 40/385001  
info@datalogic.se

**Austria**  
Datalogic Handelsges. mbH  
Tel. +43 2236/258820  
Fax +43 2236/258825  
office@datalogic.co.at

**Japan**  
Izumi Datalogic Co., Ltd.  
Tel. +81 78/3033400  
Fax +81 78/3033402  
idlmarke@izumi-datalogic.co.jp

**United Kingdom**  
Datalogic UK Ltd.  
Tel. +44 1582/464900  
Fax +44 1582/464999  
enquiries@datalogic.demon.co.uk

**Denmark**  
Datalogic AB  
Tel. +45 70/239970  
Fax +45 70/239972  
info@datalogic.se

**Netherlands**  
Datalogic Optic Electronics BV  
Tel. +31 346/572888  
Fax +31 346/568736  
info@datalogic.nl

**U.S.A.**  
Datalogic Inc.  
Tel. +1 859/6897000  
Fax +1 859/3344970  
info@datalogic.com

**France**  
Datalogic France S.A.  
Tel. +33 1/60921111  
Fax +33 1/60921340  
info@datalogic.fr

**Spain**  
Datalogic Iberia  
Tel. +34 91/3837755  
Fax +34 91/3837962  
dliberia@datalogic.it

### Datalogic Quality Partner

