



Lynx™

Hand-Held 2D Reader

FEATURES

- Omni-directional scanning
- Support most popular 1D, 2D and Postal codes
- Autodiscrimination of linear and 2D codes
- Image capture
- Intuitive aiming
- Multi-standard interface

APPLICATIONS

- Shop floor:
 - WIP
 - Tracking
 - Quality Control
- Document handling:
 - Front-Desk/Postal applications
 - Shipping & Receiving

GENERAL DESCRIPTION

Datalogic, the leading European manufacturer of Hand-Held CCD and Laser readers, further improves its offer with the introduction of a state-of-the-art and powerful "bi-dimensional" reader: the **Lynx™**.

Based on a matricial CCD sensor (640 x 480 pixel), the **Lynx™** allows "omnidirectional" reading of the most common 1D symbologies as well as a wide variety of 2D and stacked codes. Furthermore, the **Lynx™** can be used for "image-based" applications like signature capture, OCR and so on. In fact, with the **Lynx™** the user captures the whole image of the object to be identified no matter how it is orientated, thus avoiding any alignment constraint between the reader and the symbol/image to be read/captured.

The captured image can be processed on board for 1D or 2D symbologies, or downloaded in different formats for image processing on the host side.

Aiming at the image to be captured is really easy and intuitive thanks to the "double-click" trigger for Point & Read, and to the "five dot pointer" that mark the four corners and center of the reading area.

The **Lynx™** is available in two models that are specifically addressed to standard (D302) and high resolution (D302 E) codes. Both models are equipped with a multi-standard interface to allow connection to the host via RS232 or wedge emulation interface.

The software tool "visual setup" included in the **Lynx™** package allows easy configuration of all the parameters for personalizing the reader to the application, as well as a quick view of the downloaded images.

The **Lynx™** is suitable for applications in even the most demanding environments thanks to its rugged case and "Industrial" electromagnetic protection. The **Lynx's™** Firmware can be in-field updated for easy maintenance and investment protection.



MODELS AND ACCESSORIES

MODEL	DESCRIPTION	ORDER NO.	
LYNX™ D302	2D Hand-Held reader	901601010	
LYNX™ D302 E	2D Hand-Held reader for High Resolution codes	901601020	
ACCESSORIES			
		COILED CAB. STRAIGHT CAB.	
CAB362	RS232 cable, 9-pin female connector (DCE config.)	●	90A051330
CAB363*	RS232 cable, 25-pin female connector (DCE config.)	●	90A051340
CAB364*	RS232 cable, 25-pin male connector (DTE config.)	●	90A051350
CAB327	RS232 cable, 9-pin female connector (DCE config.)	●	90G001070
CAB328*	RS232 cable, 25-pin female connector cable (DCE config.)	●	90G001080
CAB320*	RS232 cable, 25-pin male connector (DTE config.)	●	90G001000
CAB391	IBM/PS2 wedge minidin external power supply	●	90A051740
Operator's Manual	Software manual for Lynx™ series		included
PG110 (110 Vac)	Power supply unit 12 VDC		B9751057
PG220 (220 Vac)	Power supply unit 12 VDC		B9751027

*Power supply available on pin 9 or 25 of the connector.

SPECIFICATIONS

POWER SUPPLY	10 to 30 VDC	BAR CODES	
CONSUMPTION	200mA @ 12V (stand-by) 300 mA@12 VDC (typical) 440 mA@12 VDC (peak current)	1D Codes	2/5 Interleaved, Code 39, Code 128, Code 93, UPC/EAN/JAN, Codabar, RSS
AIMING	Visible laser diode @ 650 nm	2D Codes	PDF417, MaxiCode, DataMatrix (ECC200), QR, AZTEC
MAX. RESOLUTION		Postal	Postnet, Planet, Australian, Japanese
D302	linear: 5 mils; datamatrix: 10 mils	IMAGE AND	640 x 480 VGA (8 bit gray scale)
D302 E	linear: 3 mils; datamatrix: 5 mils	SIGNATURE CAPTURE	320 x 240 CIF (8 bit gray scale)
READING FIELD	28.6° (H) x 21.9° (V): D302 model 21.8° (H) x 16.2° (V): D302 E model	INTERFACES	RS232, Wedge AT IBM
PRINT CONTRAST VALUE (min.)	PCS=23% (D302); PCS=45% (D302 E)	DIMENSIONS	203 x 117.2 x 68.9 mm
READING ANGLE		WEIGHT	265 g (without cable)
Skew	±40° (D302); ±60° (D302 E)	AMBIENT LIGHT IMMUNITY	0 to 100,000 lux (D302)
Pitch	±35° (D302); ±50° (D302 E)	OPERATING TEMP.	0 to 40 °C
Tilt	360° (D302/D302 E)	STORAGE TEMP.	-20 to 70 °C
SENSOR	640 X 480 element, 2D CCD array	HUMIDITY	0 to 95% non condensing
		DROP RESISTANCE	IEC 68-2-32 Test ED

READING CHARACTERISTICS

Lynx™ D302	1D CODE	DEPTH OF FIELD	Lynx™ D302 E	1D CODE	DEPTH OF FIELD
	Code 39 5 mils	75 to 105 mm		Code 39 5 mils	35 to 70 mm
	Code 39 20 mils	75 to 325 mm			
	EAN13 13 mils	45 to 115 mm			
Lynx™ D302	2D CODE	DEPTH OF FIELD	Lynx™ D302 E	2D CODE	DEPTH OF FIELD
	Postnet 20 mils	75 to 325 mm		PDF417 5 mils	40 to 75 mm
	PDF417 6.6 mils	45 to 160 mm		PDF417 10 mils	45 to 100 mm
	PDF417 10 mils	35 to 215 mm		QR 5 mils	45 to 60 mm
	QR 10 mils	55 to 105 mm		QR 10 mils	35 to 85 mm
	QR 15 mils	45 to 175 mm		Datamatrix 5 mils	45 to 60 mm
	Datamatrix 10 mils	60 to 120 mm		Datamatrix 10 mils	35 to 85 mm
	Datamatrix 15 mils	45 to 165 mm			



Product and company names and logos referenced may be either trademarks or registered trademarks of their respective companies.

We reserve the right to make modifications and improvements

Datalogic S.p.A.

Italy
Corporate Headquarters
Tel. +39 051/3147011
Fax +39 051/726562
info@datalogic.it

Sales Italy
Tel. +39 051/3147300
Fax +39 051/726562
venditeitalia@datalogic.it

Sales International
(Central and South America, Far East, Middle East - Africa)
Tel. +39 041/5986511
Fax +39 041/5986550
sales-intl@datalogic.it

Australia

Datalogic PTY LTD.
Tel. +61 3/95589299
Fax +61 3/95589233
sales@datalogic.com.au

Germany

Datalogic GmbH
Tel. +49 7026/6080
Fax +49 7026/5746
info@datalogic.de

Sweden

Datalogic AB
Tel. +46 40/385000
Fax +46 40/385001
info@datalogic.se

Austria

Datalogic Handelges MBH
Tel. +43 2236/258820
Fax +43 2236/258825
office@datalogic.co.at

Japan

Izumi Datalogic Co., Ltd.
Tel. +81 78/2723400
Fax +81 78/2722003
idlmarke@izumi-datalogic.co.jp

United Kingdom

Datalogic UK Ltd.
Tel. +44 1582/464900
Fax +44 1582/464999
enquires@datalogic.demon.co.uk

Denmark

Datalogic AB
Tel. +45 44/209970
Fax +45 44/209972
info@datalogic.se

Netherlands

Datalogic Optic Electronics BV
Tel. +31 346/572888
Fax +31 346/568736
info@datalogic.nl

U.S.A.

Datalogic Inc.
Tel. +1 859/6897000
Fax +1 859/3344970
info@datalogic.com

France

Datalogic France S.A.
Tel. +33 1/60921111
Fax +33 1/60921340
dlfrance@worldnet.fr

Spain

Datalogic España
Tel. +34 93/4335253
Fax +34 93/4335254
datalogic@sei.es

Datalogic Quality Partner